

Printing date 07.03.2024

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 5 (replaces version 4)

Revision: 07.03.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: Mipa 2K-HS-Klarlack CC 12
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Paint
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: MIPA SE
 Am Oberen Moos 1
 D-84051 Essenbach
 Tel.: +49 8703 92 20
 Fax.: +49 8703 92 21 00
 e-mail: sdb-registratur@mipa-paints.com
 www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3

H226 Flammable liquid and vapour.

health hazard

H361 Suspected of damaging fertility or the unborn child.



Repr. 2

Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



· Signal word Warning

• *Hazard-determining components of labelling:* 5-methylhexan-2-one n-Butyl acetate 2-Methoxy-1-methylethyl acetate Reaction mass of pentamethyl-piperidylsebacate

(Contd. on page 2)

GB



according to 1907/2006/EC, Article 31

Printing date 07.03.2024

Version number 5 (replaces version 4)

Revision: 07.03.2024

Trade name: Mipa 2K-HS-Klarlack CC 12

(Contd. of page 1) Hazard statements H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H361 Suspected of damaging fertility or the unborn child. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. · Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

 Dangerous components: 		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate 🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336, EUH066	10-25%
CAS: 110-12-3 EINECS: 203-737-8 Reg.nr.: 01-2119472300-51	5-methylhexan-2-one	<i>≥</i> 3-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	2.5-<5%
EC number: 918-167-1 Reg.nr.: 01-2119472146-39	Hydrocarbons, C11-C12, isoalkanes, <2% aromatics Flam. Liq. 3, H226;	<2.5%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reaction mass of pentamethyl-piperidylsebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	<i>≥</i> 0.25-<1%
CAS: 77-99-6 EINECS: 201-074-9	1,1,1-Trimethylolpropane	<1%
· Additional information: Fo	r the wording of the listed hazard phrases refer to section 1	6.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

GB



according to 1907/2006/EC, Article 31 Version number 5 (replaces version 4)

Revision: 07.03.2024

(Contd. of page 2)

Printing date 07.03.2024

Trade name: Mipa 2K-HS-Klarlack CC 12

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

⁻ GB



according to 1907/2006/EC, Article 31

Revision: 07.03.2024

Printing date 07.03.2024

Version number 5 (replaces version 4)

Trade name: Mipa 2K-HS-Klarlack CC 12

(Contd. of page 3)

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 3

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

110-12-3 5-methylhexan-2-one

WEL Short-term value: 475 mg/m³, 100 ppm Long-term value: 95 mg/m³, 20 ppm Sk

108-65-6 2-Methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

112-07-2 2-Butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm Sk

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately. **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

GB



according to 1907/2006/EC, Article 31

Revision: 07.03.2024

Printing date 07.03.2024

Version number 5 (replaces version 4)

Trade name: Mipa 2K-HS-Klarlack CC 12

(Contd. of page 4)

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chen	nical properties
· General Information	nical properties
Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and	Undetermined.
boiling range	124-128 °C (123-86-4 n-Butyl acetate)
· Flammability	Flammable.
· Lower and upper explosion limit	
	1.2 Vol % (123-86-4 n-Butyl acetate)
· Lower: · Upper:	7.5 Vol % (123-86-4 n-Butyl acetate)
	27 °C (DIN EN ISO 1523:2002)
· Flash point:	370 °C (DIN 51794, 123-86-4 n-Butyl acetate)
• Auto-ignition temperature:	Not determined.
· Decomposition temperature:	
· pH	Not determined.
· Viscosity:	22.25 \circ (DIN 52211(4)
· Kinematic viscosity at 20 °C	32-35 s (DIN 53211/4)
· Dynamic:	Not determined.
Solubility	Not missible or difficult to miss
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log	Not data was in a d
value)	Not determined.
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)
Vapour pressure at 50 °C:	55 hPa
Density and/or relative density	
Density at 20 °C:	1 g/cm ³ (DIN EN ISO 2811-1)
Relative density	Not determined.
· Vapour density	Not determined.
• 9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	lth
and environment, and on safety.	
- Ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of
1 hh	explosive air/vapour mixtures are possible.
· Solvent content:	
· VOC (EC)	40.31 %
Solids content (weight-%):	59.7 %
	(Contd. on page 6)



according to 1907/2006/EC, Article 31

Revision: 07.03.2024

Printing date 07.03.2024

03.2024 Version number 5 (replaces version 4)

Trade name: Mipa 2K-HS-Klarlack CC 12

		(Contd. of page §
· Change in condition		
· Evaporation rate	Not determined.	
· Information with regard to physical haz	ard	
classes		
· Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
[·] Gases under pressure	Void	
· Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
• Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
• Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
• Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- · Reproductive toxicity Suspected of damaging fertility or the unborn child.
- STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- Endocrine disrupting properties
- None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 7)

GB



according to 1907/2006/EC, Article 31

Revision: 07.03.2024

Printing date 07.03.2024

Version number 5 (replaces version 4)

Trade name: Mipa 2K-HS-Klarlack CC 12

(Contd. of page 6) · 12.4 Mobility in soil No further relevant information available. · 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. • vPvB: Not applicable. 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties. 12.7 Other adverse effects · Remark: Harmful to fish · Additional ecological information: · General notes: Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms SECTION 13: Disposal considerations · 13.1 Waste treatment methods Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:
 Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

• 14.1 UN number or ID number • ADR, IMDG, IATA	UN1263
• 14.2 UN proper shipping name • ADR • IMDG, IATA	UN1263 PAINT PAINT
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	<i>III</i>



Printing date 07.03.2024

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 5 (replaces version 4)

Revision: 07.03.2024

Trade name: Mipa 2K-HS-Klarlack CC 12

	(Contd. of page 7)
· 14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user Hazard identification number (Kemler code) EMS Number: 	Warning: Flammable liquids. : 30 F-E,S-E
Stowage Category	A
 14.7 Maritime transport in bulk according to IMO instruments 	Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Transport category Tunnel restriction code 	5L 3 D/E
· IMDG · Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

(Contd. on page 9)

GB



according to 1907/2006/EC, Article 31

Printing date 07.03.2024

Version number 5 (replaces version 4)

Revision: 07.03.2024

Trade name: Mipa 2K-HS-Klarlack CC 12

(Contd. of page 8) H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H361f Suspected of damaging fertility. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H400 Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. H410 EUH066 Repeated exposure may cause skin dryness or cracking. Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Repr. 2: Reproductive toxicity - Category 2 Repr. 2: Reproductive toxicity - Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * Data compared to the previous version altered.