

Safety data sheet

according to UK REACH Version number 5 (replaces version 4)

Revision: 22.08.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: Mipa 2K-HS-NiN-Füller F 37
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Filler
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: MIPA SE
 Am Oberen Moos 1
 D-84051 Essenbach
 Tel.: +49 8703 92 20
 Fax.: +49 8703 92 21 00
 e-mail: sdb-registratur@mipa-paints.com
 www.mipa-paints.com
- **1.4 Emergency telephone number:** International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labelling: Pentaerythritol tetrakis(3-mercaptopropionate) Dibutyltin dilaurate
- Hazard statements
 H226 Flammable liquid and vapour.
 H317 May cause an allergic skin reaction.
 H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)



Safety data sheet

according to UK REACH Version number 5 (replaces version 4)

Revision: 22.08.2024

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 1)

 Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Store in a well-ventilated place. Keep cool. P403+P235 · 2.3 Other hazards

Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	<15%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	Trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; () STOT SE 3, H336	2.5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	1-<2.5%
CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27	Dibutyltin dilaurate Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Eye Irrit. 2, H319; Skin Sens. 1, H317	<i>≥</i> 0.25-<0.3%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<i>≥</i> 0.025-<0.25
CAS: 7575-23-7 EINECS: 231-472-8 Reg.nr.: 01-2119486981-23	Pentaerythritol tetrakis(3-mercaptopropionate) Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302; Skin Sens. 1A, H317	<i>≥</i> 0.1-<0.25%
Nog.m.: 01-2110400001-20		(Contd. on pa



according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 5 (replaces version 4)

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 2)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.

(Contd. on page 4)

GB



Safety data sheet

according to UK REACH

Revision: 22.08.2024

Version number 5 (replaces version 4)

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 3)

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

123-8	6-4 n-Butyl acetate
	Short-term value: 966 mg/m³, 200 ppm
	Long-term value: 724 mg/m³, 150 ppm
1330-	20-7 Xylene
WEL	Short-term value: 441 mg/m ³ , 100 ppm
	Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
108-6	5-6 2-Methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m³, 50 ppm Sk
100-4	1-4 Ethylbenzene
WEL	Short-term value: 552 mg/m³, 125 ppm
	Long-term value: 441 mg/m³, 100 ppm
	Sk
	7-2 2-Butoxyethyl acetate
WEL	Short-term value: 332 mg/m³, 50 ppm
	Long-term value: 133 mg/m³, 20 ppm Sk
77 50	
	-7 Dibutyltin dilaurate
WEL	Short-term value: 0.2 mg/m ³
	Long-term value: 0.1 mg/m³ as Sn; Sk
-	dients with biological limit values:
	20-7 Xylene
BMG	/ 650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift Parameter: methyl hippuric acid
Addia	
Aaan	ional information: The lists valid during the making were used as basis.
8.2 E	xposure controls

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

(Contd. on page 5)

GB



according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024 Version number 5 (replaces version 4)

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 4)

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye/face protection



Tightly sealed goggles

9.1 Information on basic physical and chen General Information	nical properties
Physical state	Fluid
Colour:	According to product spec
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	
boiling range	124-128 °C (123-86-4 n-E
Flammability	Flammable
Lower and upper explosion limit	
Lower:	1.2 Vol % (123-86-4 n-Bu
Upper:	7.5 Vol % (123-86-4 n-Bu
Flash point:	24 °C (DIN EN ISO 1523:
Auto-ignition temperature:	>350 °C (DIN 51794, Hya
Decomposition temperature:	Not determined.
oH	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	>60 s (DIN 53211/4)
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure at 20 °C:	<15 hPa (Hydroxy acrylic
Vapour pressure at 50 °C:	55 hPa

cification

Butyl acetate)

utyl acetate) utyl acetate) :2002) droxy acrylic resin)

mix.

resin)

(Contd. on page 6)



according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 5 (replaces version 4)

Trade name: Mipa 2K-HS-NiN-Füller F 37

	(Contd. of page
Density and/or relative density	
Density at 20 °C:	1.476 g/cm³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	26.92 %
Solids content (weight-%):	73.1 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haza classes	ard
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

 \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB



according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 5 (replaces version 4)

Trade name: Mipa 2K-HS-NiN-Füller F 37

· Respiratory or skin sensitisation May cause an allergic skin reaction.

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information			
• 14.1 UN number or ID number • ADR, IMDG, IATA	UN1263		
14.2 UN proper shipping name			
ADR	UN1263 PAINT, ENVIRONMENTALL HAZARDOUS		
IMDG	PAINT (Trizinc bis(orthophosphate), Polythiols, MARINE POLLUTANT		
IATA	PAINT		



Safety data sheet according to UK REACH

Revision: 22.08.2024

Printing date 22.08.2024

Version number 5 (replaces version 4)

	(Contd. of page
[.] 14.3 Transport hazard class(es)	
ADR	
· Class · Label	3 (F1) Flammable liquids. 3
·IMDG	
Class	3 Flammable liquids.
· Label	3
IATA	
· Class	3 Flammable liquids.
· Label	3
14.4 Packing group ADR, IMDG, IATA	111
14.5 Environmental hazards:	Product contains environmentally hazardo
· Marine pollutant:	substances: Dibutyltin dilaurate Symbol (fish and tree)
[·] Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code	e): 30
EMS Number:	F-E, <u>S-E</u>
· Segregation groups · Stowage Category	(SGG1) Acids A
• 14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
· Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	
· Remarks:	≤ 5 l: 2.2.3.1.5 ADR
IMDG	
Limited quantities (LQ)	5L
Remarks:	≤ 5 l: 2.2.3.1.5 IMDG
UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALI HAZARDOUS

(Contd. on page 9)

GB



Safety data sheet

according to UK REACH Version number 5 (replaces version 4)

Revision: 22.08.2024

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 8)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- [.] Poisons Act

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

- P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.



Safety data sheet

according to UK REACH Version number 5 (replaces version 4)

Revision: 22.08.2024

Trada nama: Mina 2K US NiN Füllar

Trade name: Mipa 2K-HS-NiN-Füller F 37

(Contd. of page 9) Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A Muta. 2: Germ cell mutagenicity – Category 2 Repr. 1B: Reproductive toxicity – Category 1B STOT SE 1: Specific target organ toxicity (single exposure) - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * Data compared to the previous version altered.