

ing Systems

Printing date 02.10.2024

according to UK REACH Version number 9 (replaces version 8)

Safety data sheet

Revision: 02.10.2024

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: Mipa V.I.P. Exclusive Basecoat
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- Sector of Use
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Product category** PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Paint
- 1.3 Details of the supplier of the safety data sheet
 Manufacturer/Supplier: MIPA SE
 Am Oberen Moos 1
 D-84051 Essenbach
 Tel.: +49 8703 92 20
 Fax.: +49 8703 92 21 00
 e-mail: sdb-registratur@mipa-paints.com
 www.mipa-paints.com
 • 1.4 Emergency telephone number: International emergency number: +49(0)700 24112112 (MIP)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation. **Hazard pictograms**



· Signal word Warning

- Hazard-determining components of labelling: n-Butyl acetate 2-Methoxy-1-methylethyl acetate Methyl ethyl ketone
- · Hazard statements
- H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Safety data sheet

according to UK REACH Version number 9 (replaces version 8)

Revision: 02.10.2024

Trade name: Mipa V.I.P. Exclusive Basecoat

(Contd. of page 1)

 Precautionary state 	atements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
· Additional inforn	nation:
EUH066 Repeated	d exposure may cause skin dryness or cracking.
2.3 Other hazard	5

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 123-86-4	n-Butyl acetate	50-100%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336, EUH066	
	2-Methoxy-1-methylethyl acetate 🚸 Flam. Liq. 3, H226; 🔶 STOT SE 3, H336	10-25%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
EINECS: 201-159-0	Methyl ethyl ketone Flam. Liq. 2, H225;	<2.5%
EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
	magnesium fluoride () Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<2.5%

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

⁻ GB



Safety data sheet

according to UK REACH

Version number 9 (replaces version 8)

Revision: 02.10.2024

Trade name: Mipa V.I.P. Exclusive Basecoat

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

- *Information about fire and explosion protection:* Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)



Safety data sheet

according to UK REACH Version number 9 (replaces version 8)

Revision: 02.10.2024

Printing date 02.10.2024

Trade name: Mipa V.I.P. Exclusive Basecoat

100 4	SE 6.2 Mothoxy 1 mothylathyl acatata	(Contd. of page
	65-6 2-Methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm	
	Long-term value: 274 mg/m³, 50 ppm	
	Sk	
1330	-20-7 Xylene	
WEL	Short-term value: 441 mg/m³, 100 ppm	
	Long-term value: 220 mg/m ³ , 50 ppm	
	Sk; BMGV	
78-93	3-3 Methyl ethyl ketone	
WEL	Short-term value: 899 mg/m³, 300 ppm	
	Long-term value: 600 mg/m ³ , 200 ppm	
	Sk, BMGV	
100-4	41-4 Ethylbenzene	
WEL	Short-term value: 552 mg/m³, 125 ppm	
	Long-term value: 441 mg/m ³ , 100 ppm	
	Sk	
Ingre	edients with biological limit values:	
1330	-20-7 Xylene	
BMG	V 650 mmol/mol creatinine	
	Medium: urine	
	Sampling time: post shift	
	Parameter: methyl hippuric acid	
78-93	3-3 Methyl ethyl ketone	
BMG	V 70 μmol/L	
	Medium: urine	
	Sampling time: post shift	
	Parameter: butan-2-one	
	tional information: The lists valid during the making were used as t	haaia

- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.



Safety data sheet

according to UK REACH Version number 9 (replaces version 8)

Revision: 02.10.2024

Trada nama: Mina VID Evaluaiya Ba

Trade name: Mipa V.I.P. Exclusive Basecoat

(Contd. of page 4)

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties		
General Information	, ,	
· Physical state	Fluid	
· Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
 Melting point/freezing point: 	Undetermined.	
 Boiling point or initial boiling point and 		
boiling range	124-128 °C (123-86-4 n-Butyl acetate)	
· Flammability	Flammable.	
• Lower and upper explosion limit		
· Lower:	1 Vol % (Polyester resin, hydroxy functional	
	(016))	
· Upper:	10.8 Vol % (108-65-6 2-Methoxy-1-methylethyl	
	acetate)	
· Flash point:	27 °C (DIN EN ISO 1523:2002, 123-86-4 n-Butyl	
	acetate)	
 Auto-ignition temperature: 	315 °C (DIN 51794, 108-65-6 2-Methoxy-1-	
	methylethyl acetate)	
 Decomposition temperature: 	Not determined.	
рН	Not determined.	
Viscosity:		
 Kinematic viscosity at 20 °C 	>60 s (ISO 6 mm)	
· Dynamic:	Not determined.	
· Solubility		
water:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water (log		
value)	Not determined.	
Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-Butyl acetate)	
Vapour pressure at 50 °C:	55 hPa	
Density and/or relative density		
Density at 20 °C:	0.946 g/cm³ (DIN EN ISO 2811-1)	
Relative density	Not determined.	
· Vapour density	Not determined.	
• 9.2 Other information		
· Appearance:		
· Form:	Fluid	
· Important information on protection of heal		
and environment, and on safety.		
· Ignition temperature:	Product is not selfigniting.	
• Explosive properties:	Product is not explosive. However, formation of	
	explosive air/vapour mixtures are possible.	
	(Contd. on page 6)	



Safety data sheet

according to UK REACH

Revision: 02.10.2024

Printing date 02.10.2024

Version number 9 (replaces version 8)

Trade name: Mipa V.I.P. Exclusive Basecoat

	(C	ontd. of page
Solvent content:		
VOC (EC)	73.97 %	
Solids content (weight-%):	26.0 %	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical haz	ard	
classes		
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

• **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

123-86-4 n-Butyl acetate

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rabbit)

STOT-single exposure May cause drowsiness or dizziness.

11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

(Contd. on page 7)



Safety data sheet

according to UK REACH Version number 9 (replaces version 8)

Revision: 02.10.2024

Trade name: Mipa V.I.P. Exclusive Basecoat

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Endocrine disrupting properties
- For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.


SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.





Safety data sheet

according to UK REACH

Revision: 02.10.2024

•

Version number 9 (replaces version 8)

	(Contd. of page
Label	3
14.4 Packing group ADR, IMDG, IATA	///
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
<i>14.7 Maritime transport in bulk according to IMO instruments</i>	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Transport category Tunnel restriction code Remarks:	5L 3 D/E ≤ 450 I: 2.2.3.1.5 ADR
IMDG Limited quantities (LQ) Remarks:	5L ≤ 450 l: 2.3.2.5 IMDG-Code
UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
	<2.5
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

GB



Safety data sheet

according to UK REACH Version number 9 (replaces version 8)

Revision: 02.10.2024

Trade name: Mipa V.I.P. Exclusive Basecoat

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * * Data compared to the previous version altered.

GB -